USB 2.0 DOCKING STATION

USB DEVICE

Features:
- Four USB ports up to 100mA per port
- Support over current protection
- Support both High-Speed (480 Mbps), and Low-Speed (1.5 Mbps) transfer
- Truly Plug & Play automatic system
- Chains up to 127 USB devices
- USB and ACPI compliant

Specifications:
- 4 port USB 2.0 High-Speed Hub
- Interface: Universal Serial Bus (USB) Revision 2.0
- Connector: Four A type (female) connectors and one mini USB (female) connector
- Cable: One USB cable (A to mini-USB male)
- Transfer rates: High-Speed 480 Mbps, Full-Speed at 12Mb/sec and Low-Speed at 1.5Mb/sec
- Auto detect when ports are plug-in
- LED: Power LED for High-Speed. Power for AC/DC Adapter 5V (2.3A)
- Consumption current: 5V 2.5A
- Power adaptor: 100 - 240V, 50/60 Hz 0.6A (max)
- Power adapter output: 5V 2.3A
- Enclosure: Plastics
- EMI: CE & FCC
- Dimensions: 77 x 32 x 15 mm
- Weight: 25g

Package contents:
- USB 2.0 4 Port Hub
- USB cable
- Manual
- Power adapter

System requirements:
- Intel® Pentium® III or above
- 128MB of system RAM or more
- One available USB 2.0 port
- Windows® 2000, or XP
- Power supply source of 100 - 240V AC

Note:
- Your computer must have USB 2.0 Host and drivers, and support USB 2.0 Hub device. USB 2.0 Hub no need driver. Microsoft only support Windows 2000 and Windows XP in USB 2.0 High-Speed driver.

EAN Code: 40 19337 81040 0

Art. Nr. 81040